

02/01/02



# **PLUG INNER FRAME WITH TWISTED BLADES**

## **Background of the Invention**

### **1. Field of the Invention**


The present invention relates to a plug inner frame with twisted blades to reduce the manufacture cost.

### **2. Description of the Related Art**

A plug is a necessary element to all kinds of computers, electric appliances, etc and thus plays an important role in daily life. A typical plug generally comprises two or three blades or prongs. In manufacture, a wire is attached to an end of each blade, and the blades are then embedded into an inner frame. The semi-product comprised of the wires and the blades embedded in the inner frame is then placed into a mold for subsequent injection molding to form the final plug with a housing.

Most advanced countries require each blade of the plug to be partially wrapped by an insulating layer at an exposed section thereof, thereby avoiding electric shocks in case that the plug is loosened. The insulating layer is generally made of plastic material and wraps a portion of the exposed section of the blade by means of injection molding. However, the insulating layer is apt to be disengaged from the smooth metal surface of the blade as a result of poor bonding force therebetween. Thus, the insulating layer would slide easily, and sometimes may even fall. The blade is then exposed again and thus could cause an electric shock.

Fig. 1 of the drawings illustrates a conventional plug blade 1 including an enclosed section 11 and an exposed section 12. The exposed section 12 includes a wider front section 121 and a narrower rear section 122 having a transverse through-hole 123. Plastic material is filled to a face of the narrower



1 rear section 122 and flows through the transverse through-hole 123 to the other  
2 face of the narrower rear section 122. An insulating layer is formed on the  
3 narrower rear section 122 after hardening of the plastic material. The bonding  
4 force between the insulating layer and the narrower rear section 122 is  
5 improved, and the time for filling the plastic material is reduced. Fig. 2 shows  
6 another conventional plug blade 1 that is substantially identical to that of the  
7 plug blade 1 in Fig. 1, except that the upper and lower faces of the narrower  
8 rear section 122 are respectively flush with those of the wider front section  
9 121.

10 However, an end of a wire must be inserted into and thus embraced by an  
11 end of each blade of the plug before subsequent procedure. The blades must  
12 face the same direction when proceeding with this wire-inserting procedure in  
13 an associated wire-inserting machine. In some countries, the blades of a plug  
14 are twisted such that the wire-inserting grooves of the blades face different  
15 directions. The current wire-inserting machine could not proceed with the  
16 wire-inserting procedure on the plugs with twisted blades. The manufacture  
17 cost is largely increased when seeking a solution to this end. In addition, a  
18 fault (generally a shallow recess) is formed on a surface of the insulating layer  
19 after hardening of the plastic material. The appearance of the plug is thus  
20 adversely affected.

### 21 **Summary of the Invention**

22 An object of the present invention is to provide a plug inner frame with  
23 twisted blades to reduce the manufacture cost.

24 Another object of the present invention is to provide a plug inner frame  
25 with twisted blades having an aesthetic appearance.

1 A plug inner frame in accordance with the present invention comprises a  
2 frame in the form of a block and at least two blades securely held by the frame.  
3 Each blade includes an enclosed section and an exposed section. Each blade  
4 includes an end having a wire-receiving groove. A neck is defined between the  
5 wire-receiving groove and the exposed section. The neck of each blade is so  
6 twisted that the wire-receiving grooves of the blades face the same direction.

7 Other objects, advantages, and novel features of the invention will become  
8 more apparent from the following detailed description when taken in  
9 conjunction with the accompanying drawings.

#### 10 **Brief Description of the Drawings**

11 Fig. 1 is a perspective view of a conventional plug blade.

12 Fig. 2 is a perspective view of another conventional plug blade.

13 Fig. 3 is a perspective view of a first embodiment of a plug inner frame in  
14 accordance with the present invention.

15 Fig. 4 is a perspective view of a second embodiment of the plug inner  
16 frame in accordance with the present invention.

17 Fig. 5 is a perspective view of a third embodiment of the plug inner frame  
18 in accordance with the present invention.

19 Fig. 6 is a perspective view of a fourth embodiment of the plug inner  
20 frame in accordance with the present invention.

21 Fig. 7 is a perspective view illustrating a raw material for the plug blade.

22 Fig. 8 is a perspective view illustrating a semi-product of the plug blade in  
23 Fig. 7.

24 Fig. 9 is a perspective view illustrating the semi-product of Fig. 8 having  
25 an insulating layer formed thereon.

1           Fig. 10 is a perspective view of a final plug made from the plug inner  
2 frame in Fig. 3.

3           Fig. 11 is a perspective view of a final plug made from the plug inner  
4 frame in Fig. 6.

5           Fig. 12 is a perspective view of a final plug made from the plug inner  
6 frame in Fig. 4.

7           Fig. 13 is a perspective view of a final plug made from the plug inner  
8 frame in Fig. 5.

9           Fig. 14 is a perspective view of a fifth embodiment of the plug inner frame  
10 in accordance with the present invention.

11          Fig. 15 is a perspective view of a sixth embodiment of the plug inner  
12 frame in accordance with the present invention.

13          Fig. 16 is a perspective view of a seventh embodiment of the plug inner  
14 frame in accordance with the present invention.

15          Fig. 17 is a perspective view of an eight embodiment of the plug inner  
16 frame in accordance with the present invention.

17          Fig. 18 is a perspective view illustrating another raw material for the plug  
18 blade.

19          Fig. 19 is a perspective view illustrating a semi-product of the plug blade  
20 in Fig. 18.

21          Fig. 20 is a perspective view illustrating the semi-product of Fig. 19  
22 having an insulating layer formed thereon.

23          Fig. 21 is a perspective view of a final plug made from the plug inner  
24 frame in Fig. 14.

25          Fig. 22 is a perspective view of a final plug made from the plug inner  
26 frame in Fig. 17.

1 Fig. 23 is a perspective view of a final plug made from the plug inner  
2 frame in Fig. 15.

3 Fig. 24 is a perspective view of a final plug made from the plug inner  
4 frame in Fig. 16.

5 Fig. 25 is a perspective view of an embodiment modified from the  
6 semi-product of the plug blade of Fig. 9.

7 Fig. 26 is a perspective view of an embodiment modified from the  
8 semi-product of the plug blade of Fig. 20.

### 9 **Detailed Description of the Preferred Embodiments**

10 Fig. 7 illustrates a raw material of a plug blade 22 for manufacturing a  
11 plug inner frame (Figs. 3 and 6) of a final plug in accordance with the present  
12 invention. The plug blade 22 includes an enclosed section 221 to be enclosed  
13 by a housing (not labeled, see Figs. 3 and 6) and an exposed section 222. The  
14 exposed section 222 includes a wider front section 223 and a narrower rear  
15 section 224. A transverse through-hole 226 extends from a face of the  
16 narrower rear section 224 to the other face of the narrower rear section 224. A  
17 reinforcing guide slot 227 is defined in the narrower rear section 224 and  
18 communicated with the transverse through-hole 226. Also, the reinforcing  
19 guide slot 227 extends from a face of the narrower rear section 224 to the other  
20 face of the narrower rear section 224. The enclosed section 221 includes a  
21 shallow recess 225 in a front end thereof for filling plastic material into the  
22 narrower rear section 224. The faces of the narrower rear section 224 are lower  
23 than those of the wider front section 223, and two lateral sides of the narrower  
24 rear section 224 are lower than those of the wider front section 223.

1 A wire-receiving groove 228 is defined in a rear end of the enclosed  
2 section 221. A neck 229 is formed between the wire-receiving groove 228 and  
3 the exposed section 222.

4 The neck 229 of the plug blade 22 in Fig. 7 is twisted to form a plug blade  
5 22 shown in Fig. 8 such that the wire-receiving groove 228 faces upward for  
6 allowing easy insertion of an end of a wire. Next, an insulating layer 220 is  
7 formed on the narrower rear section 224, as shown in Fig. 9. It is achieved by  
8 means of filling molten plastic material into the narrower rear section 224 via  
9 the shallow recess 225. The molten plastic material flows from a face to the  
10 other face of the narrower rear section 224 via the transverse through-hole 226  
11 and the slot 227. The insulating layer 220 is formed after hardening of the  
12 plastic material.

13 Next, two of the plug blades 22 in Fig. 8 can be placed into a mold, and  
14 plastic material is injected into the mold to form an inner frame 2 comprising a  
15 frame 21 in the form of a plug and two plug blades 22 securely held by the  
16 frame 21, best shown in Fig. 3. Fig. 10 is a perspective view of a final plug 3A  
17 made from the plug inner frame 2 in Fig. 3 after an injection molding  
18 procedure. Alternatively, the plug blade 22 in Fig. 9 can be used to form an  
19 inner frame 2C shown in Fig. 6. The inner frame 2C includes a frame 21C, two  
20 blades 22C, and a grounding prong 4A. Fig. 11 is a perspective view of a final  
21 plug 3B made from the plug inner frame 2C in Fig. 6 after an injection  
22 molding procedure.

23 Fig. 25 illustrate an embodiment modified from the embodiment of Fig. 9,  
24 wherein the hole in the exposed section 222 in Fig. 9 is omitted, and the  
25 wire-receiving groove 228 is in the form of a circle. The plug blade 22 in Fig.  
26 25 can be used to form an inner frame 2A shown in Fig. 4. The inner frame 2A

1 includes a frame 21A and two blades 22A. Fig. 12 is a perspective view of a  
2 final plug 3C made from the plug inner frame 2A in Fig. 4 after an injection  
3 molding procedure. Alternatively, the plug blade 22 in Fig. 25 can be used to  
4 form an inner frame 2B shown in Fig. 5. The inner frame 2B includes a frame  
5 21B, two blades 22B, and a grounding prong 4. Fig. 13 is a perspective view  
6 of a final plug 3D made from the plug inner frame 2B in Fig. 5 after an  
7 injection molding procedure.

8 Fig. 18 illustrates another embodiment of a raw material of a plug blade 22  
9 for manufacturing a plug inner frame (Figs. 14 and 17) in accordance with the  
10 present invention. The plug blade 22 includes an enclosed section 221 to be  
11 enclosed by a housing (not labeled, see Figs. 14 and 17) of a final plug and an  
12 exposed section 222. The exposed section 222 includes a wider front section  
13 223 and a narrower rear section 224. A transverse through-hole 226 extends  
14 from a face of the narrower rear section 224 to the other face of the narrower  
15 rear section 224. A reinforcing guide slot 227 is defined in the narrower rear  
16 section 224 and communicated with the transverse through-hole 226. Also, the  
17 reinforcing guide slot 227 extends from a face of the narrower rear section 224  
18 to the other face of the narrower rear section. The enclosed section 221  
19 includes a shallow recess 225 in a front end thereof for filling plastic material  
20 into the narrower rear section 224. The faces of the narrower rear section 224  
21 are flush with those of the wider front section 223, and two lateral sides of the  
22 narrower rear section 224 are lower than those of the wider front section 223.

23 A wire-receiving groove 228 is defined in a rear end of the enclosed  
24 section 221. A neck 229 is formed between the wire-receiving groove 228 and  
25 the exposed section 222.

1        The neck 229 of the plug blade 22 in Fig. 18 is twisted to form a plug  
2 blade 22 shown in Fig. 19 such that the wire-receiving groove 228 faces  
3 upward for allowing easy insertion of an end of a wire. Next, an insulating  
4 layer 220 is formed on the narrower rear section 224, as shown in Fig. 20. It is  
5 achieved by means of filling molten plastic material into the narrower rear  
6 section 224 via the shallow recess 225. The molten plastic material flows from  
7 a face to the other face of the narrower rear section 224 via the transverse  
8 through-hole 226 and the slot 227. The insulating layer 220 is formed after  
9 hardening of the plastic material.

10        Next, two of the plug blades 22 in Fig. 20 can be placed into a mold, and  
11 plastic material is injected into the mold to form an inner frame 2 comprising a  
12 frame 21 in the form of a block and two plug blades 22, best shown in Fig. 14.  
13 Fig. 21 is a perspective view of a final plug 3A made from the plug inner  
14 frame 2 in Fig. 14 after an injection molding procedure. Alternatively, the plug  
15 blade 22 in Fig. 20 can be used to form an inner frame 2C shown in Fig. 17.  
16 The inner frame 2C includes a frame 21C, two blades 22C, and a grounding  
17 prong 4A. Fig. 22 is a perspective view of a final plug 3B made from the plug  
18 inner frame 2C in Fig. 17 after an injection molding procedure.

19        Fig. 26 illustrate an embodiment modified from the embodiment of Fig. 20,  
20 wherein the hole in the exposed section 222 in Fig. 20 is omitted, and the  
21 wire-receiving groove 228 is in the form of a circle. The plug blade 22 in Fig.  
22 26 can be used to form an inner frame 2A shown in Fig. 15. The inner frame  
23 2A includes a frame 21A and two blades 22A. Fig. 23 is a perspective view of  
24 a final plug 3C made from the plug inner frame 2A in Fig. 15 after an injection  
25 molding procedure. Alternatively, the plug blade 22 in Fig. 26 can be used to  
26 form an inner frame 2B shown in Fig. 16. The inner frame 2B includes a frame

1 21B, two blades 22B, and a grounding prong 4. Fig. 24 is a perspective view  
2 of a final plug 3D made from the plug inner frame 2B in Fig. 16 after an  
3 injection molding procedure.

4 According to the above description, it is noted that the procedure for a  
5 current wire-inserting machine needs no change, as the inner frame 2, 2A, 2B,  
6 2C in accordance with the present invention with twisted blades 22, 22A, 22B,  
7 22C allows the wire-receiving holes 228 to face the same direction. The fault  
8 resulting from the formation of the insulating layer is located in a position  
9 adjacent to the shallow recess 225 for filling the molten plastic material.  
10 Nevertheless, the shallow recess 225 is enclosed by the housing after  
11 formation of the whole plug 3A, 3B, 3C, 3D. Thus, the appearance of the  
12 insulating layer is not adversely affected. Further, due to provision of the  
13 reinforcing guide slot 227 communicated with the transverse through-hole 226,  
14 the air on the faces of the metal blade can be well expelled, and the molten  
15 plastic material flowing randomly on the faces of the metal blades may flow  
16 from one face to the other of each metal blade. Thus, the thickness of the  
17 insulating layer is more uniform after formation. Further, the overall structure  
18 of the plug blade has appropriate rigidity from metal and appropriate softness  
19 from the plastic material, thereby having an optimal resistance to bending. The  
20 finally formed plugs 3A, 3B, 3C, and 3D meet requirements of different  
21 countries.

22 Although the invention has been explained in relation to its preferred  
23 embodiment, it is to be understood that many other possible modifications and  
24 variations can be made without departing from the scope of the invention as  
25 hereinafter claimed.  
26